

## VISTA MODULAR FURNITURE SPEC SHEET

**Desk/Table Shells:** Work surfaces are 1 ¼" thick, 45#-48# density M3 grade commercial wood core, provided with high- pressure laminate top balanced backer sheet, with T-Edge mold. Optional PVC edge, self-edge or post form waterfall edging available. Standard with two 3" x 1 ½" grommets one at each rear corner for rectangular work surfaces. Modesty panel is 20 gauge multi formed cold rolled steel with a 4 ½" high x 1 1/8" deep cable channel welded onto the upper section, placing it directly under the work surface, allowing for cable exit at each end, accessing the grommets cable pass through in the end of each leg. Modesty panel standard with 3 ht options, F- 27 ½" high full height, H- 21 ½" ¾ height, and X-21 ½" wall access open frame. Support legs are 2" thick. Vertical components are 20gauge cold rolled steel with multi-formed construction for reinforcement. Support legs standard with full end panel, C Leg, Clear access leg, and shared C and clear access legs. Horizontal foot and attachment arm are 18 gauge, channeled formed and welded to the vertical members. Full-length 16 gauge U-channel component is welded into the foot giving strength to the adjustable floor glide and further strengthening the entire foot member as well as vertical uprights. Each support leg offers two inside and outside pass throughs horizontally, except for the full end panel, which offers two inside grommets. 1" adjustable floor glides under each leg support are standard.

**Risers:** See "Vista Standard Riser Specification Sheet" or "Vista Stacks Riser Specification Sheet" for riser details.

**Pedestals:** See "Ultra Pedestal Specification Sheet" or "ES Series Pedestal Specification Sheet" for pedestal details.

**Finish:** All Invincible<sup>™</sup> steel products are processed through a 5-stage industrial washer to remove oil and organics from the surface while applying an iron phosphate conversion coating to promote adhesion and corrosion resistance as a pre-paint treatment. In addition, parts are rinsed with a non-chrome sealer to aid in paint adhesion and to further protect the metal. **The surface is then painted with environmentally-friendly and highly durable hybrid powder coat paint applied electro-statically and cured at high temperature.** Invincible<sup>™</sup> products are available in a full assortment of standard Invincible<sup>™</sup> colors, both smooth and textured finishes, as well as special order colors.