

## FREEDOM SERIES TRAINING TABLE SPEC SHEET

Work surfaces are 1-1/4" thick (overall thickness), including 45#-48# density M3 commercial grade wood core, high pressure laminate on the top side with protective balancing sheet on underside of surface.

PVC edge (-PV) is standard. T-Mold edge (-TE) is also available. "SE" self-edge or post form "WF" waterfall edging are optional. Optional grommets available. See Table EZ Order Form for (2) standard grommet locations, or consult with Customer Service.

T-Leg and C-Leg are made of 14 gauge, 2" diameter powder coat painted steel tubing, welded to 12 gauge 6-11/16" x 5-13/16 plate that attaches to the underside of the top. Four adjustable floor glides are standard. Grommets are available as an option. Consult with the factory regarding number and placement of grommets.

**Finish:** All Invincible<sup>™</sup> steel products are processed through a 5-stage industrial washer to remove oil and organics from the surface while applying an iron phosphate conversion coating to promote adhesion and corrosion resistance as a pre-paint treatment. In addition, parts are rinsed with a non-chrome sealer to aid in paint adhesion and to further protect the metal. The surface is then painted with **environmentally-friendly and highly durable hybrid powder coat paint applied electrostatically and cured at high temperature.** Invincible<sup>™</sup> products are available in a full assortment of standard Invincible<sup>™</sup> colors, both smooth and textured finishes, chemical-resistant finishes, as well as special order colors.